

Weltweit schlankstes Videowall-Display mit Randabstand von 0,88 mm

TH-55VF2H

Ideale Lösung für große, fesselnde Videowalls mit extrem schmalen Rahmen und den Einsatz in den Bereichen Digital Signage, Broadcast und Leitstellen.



KEY FEATURES

- Rahmenloses D-LED LCD-Display (55 Zoll), 500 cd/m², Randabstand 0,88 mm, 24/7-Dauerbetrieb, IPS-Panel mit blendfreier Oberfläche (Dunst 28 %).
- Modernste Gleichmäßigkeit für einheitlich hohe Bildqualität.
- Widerstandsfähige Failover- und Failback-Funktion mit vereinfachtem Workflow
- Unterstützt Reverse-Scan und Frame-Steuerung für verbesserte Multi-Screen-Video-Sichtbarkeit
- Supports reverse scan and frame control to improve multi-screen video visibility

Unübertroffen nahtlose Videowalls



SPECIFICATIONS

| | |
|-------------------------------|---|
| Gewicht | approx. 23.0 kg / approx. 50.7 lbs |
| Dimensions (W x H x D) | 1210.6 x 681.3 x 97.3 mm / 47.658" x 26.820" x 3.829" |
| Helligkeit | 700 cd/m ² |
| Contrast Ratio | 1100:1 |
| Aspect Ratio | 16:9 |
| Response Time | 8.0 ms (G to G) |
| Viewing Angle | 178° / 178° (CR ≥ 10) |

| | |
|--|--|
| Effective Display Area (W x H) | 1209.6 x 680.3 mm(47.62" x 26.78") |
| Panel Type | IPS/D-LED |
| Bezel Width | T / B / R / L 0.44 mm / 0.018" |
| Wall-Hanging Pitch | VESA Compliant 400 x 400 mm / 15.8" x 15.8" (Installed by: M6 screws / Screw hole depth 12 mm / 0.47") |
| Screen Size | 54.6-inch (1387 [?]?) |
| Panel Surface Treatment | Advanced Anti-glare treatment (Haze 28%) |
| Terminals LAN | RJ45 x 1 / x 1, 100BASE-TX, Compatible with PJLinkTM (Shared with DIGITAL LINK?) |
| Terminals HDMI In | Type A Connector x 1 |
| Terminals USB | USB 2.0 Type A connector x 1 DC 5 V / 500 mA (USB3.0 is not supported.) |
| Terminals Audio Out | Stereo Mini Jack (M3) x 1 Variable (-∞ - 0 dB) (1 kHz 0 dB Input, 10 k Ω Load) |
| Terminals DVI-D IN/AUDIO IN (L/R) | DVI-D 24-pin x2 |
| Terminals IR In/Out | Stereo Mini Jack (M3) x 1 / x 1 |
| Terminals DisplayPort IN | DisplayPort? DP1.1 Dual Mode Only) x 1 |
| Terminals Serial In/Out | D-sub 9pin x 1 / x 1, RS-232C Compatible |
| Operating Time | 24 h/day |
| Operating Environment | 0°C to 40°C / 32°F to 104°F /for up to 1400 m (4593 ft) altitude 0°C to 35°C / 32°F to 95°F /for between 1400 m (4593 ft) and 2800 (9186 ft) m altitude Depending on the temperature or humidity conditions, uneven brightness may be observed. This is not a malfunction. |
| Resolution (H x V) | 1920 x 1080 |
| Dynamic Contrast ratio | 500000:1 |
| Speaker | ?Ω ,20 W [10 W ? 10 W]?10 % THD? |
| Audio 1 In | Stereo Mini Jack (M3) x 1 |
| Audio 2 In | L/R:Pin Jack x 1 |
| PC In | Mini D-Sub 15-pin x 1 (Female) |
| Carton Dimensions (W x H x D) | 1395 x 848 x 280 mm / 55.0" x 33.4" 11.1" |
| Gross Weight | 34 kg / 75.0 lbs |
| Terminals DIGITAL LINK | RJ45 x 1, Long Reach Mode (Shared with LAN IN?) RJ45 x 1 (Shared with LAN OUT?) |
| Audio Out | Stereo Mini Jack (M3) x 1 Variable (-∞ - 0 dB) (1 kHz 0 dB Input, 10 k Ω Load) |
| Power Consumption | 300 W |
| Power Requirements | AC 110 - 127 V 50Hz/60Hz AC 220 - 240 V, 50 Hz/60 Hz |
| Power Off Condition | approx. 0 W |
| On Mode Average Power Consumption* | 165 W |
| Stand-by Condition | approx. 0.5 W |

URL: <https://business.panasonic.de/visuelle-systeme/th-55vf2h>

CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>